

## Patch cable E2000 - GigaPATCH™

GigaPATCH™ E2000 patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools.  
100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100% of contacts
- Control of the connector Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- The connector are color coded according to i.hht IEC 60874-19, Beige for MM, Blue for SM and Green for APC.
- Production certified in i.hht. ISO9001:2002 and ISO14001:2004
- RoHS i.hht 2002/95/ES



### Dimensions and characteristics

Standards		IEC 61754-15, EN 186270, Telcordia GR-326			
IL = Insertion loss RL = Reflection loss		SM			MM
		SPC	UPC	APC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,15	0,14
Threshold	RL (dB)	>45	>50	>60	-
Typical value	RL (dB)	49	53	62	-

### Ordering Information

GCE6E60115xxxGY	Patch SPX E2000-E2000 MM 62,5/125/2000 (OM1) xM Grey LS0H
GCE5E50115xxxOR	Patch SPX E2000-E2000 MM 50/125/2000 (OM2) xM Orange LS0H
GCE3E30115xxxAQ	Patch SPX E2000-E2000 MM 50/125/2000 (OM3) xM Light blue LS0H
GCEUEU0115xxxYE	Patch SPX E2000/UPC-E2000/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCEAEA0115xxxYE	Patch SPX E2000/APC-E2000/APC SM 9/125/2000 (OS1) xM Yellow LS0H
GCE6E60215xxxGY	Patch DPX E2000-E2000 MM 62,5/125/2000 (OM1) xM Gray LS0H
GCE5E50215xxxOR	Patch DPX E2000-E2000 MM 50/125/2000 (OM2) xM Orange LS0H
GCE3E30215xxxAQ	Patch DPX E2000-E2000 MM 50/125/2000 (OM3) xM Light blue LS0H
GCEUEU0215xxxYE	Patch DPX E2000/UPC-E2000/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCEAEA0215xxxYE	Patch DPX E2000/APC-E2000/APC SM 9/125/2000 (OS1) xM Yellow LS0H

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)