

Patch cable MTRJ - GigaPATCH™

GigaPATCH™ MTRJ patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100 of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- Produktion certifierad i.hht ISO9001:2002 och ISO14001:2004
- RoHS i.hht 2002/95/ES



Dimensions and characteristics

Standards		IEC 61754-18, GR-1435	
IL = Insertion loss		SM	MM
RL = Reflection loss		SPC	-
Threshold	IL (dB)	<0,5	<0,75
Typical value	IL (dB)	0,22	0,20
Threshold	RL (dB)	>45	-
Typical value	RL (dB)	48	-

Ordering Information

GCG6G60210xxxGY	Patch MTRJ(F)-MTRJ(F) MM 62,5/125/2000 (OM1) xM Grå LSOH
GCG5G50210xxxOR	Patch MTRJ(F)-MTRJ(F) MM 50/125/2000 (OM2) xM Orange LSOH
GCG3G30210xxxAQ	Patch MTRJ(F)-MTRJ(F) MM 50/125/2000 (OM3) xM Aqua LSOH
GCGSGS0210xxxYE	Patch MTRJ(F)/SPC-MTRJ(F)/SPC SM 9/125/2000 (OS1) xM Gül LSOH

xxx: Length in meter (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

MTRJ (F): MTRJ female (without control pins)

GigaCom reserves the right to make changes in this specification without prior notice.