

## Cable Pre-terminated QXAI - GigaPATCH™


GigaPatch  $^{\text{TM}}$  pre-terminated cable with loose buffer can be supplied in MM and SM with the most common connector types. The cable is the equivalent to QXAI. It is supplied with a pulling tube that protects the fibre and it's connector during shipping and installation. The fibres in the break-out comes with a 0.9 mm tube (ref. c on the image below). Installation of the connectors is carried out i.hht. according to the latest standard, and with the last generation of test— and production tools. The cables and connectors are tested to be 100%, both visually, for RL (reflected signal) and IL (attenuation).

- Stable and high-quality
- Up to 48 fibre
- Halogen free and flam retardant cable LSFR0H
- Cable with loose buffer, to further QXAI
- fibre in the break-out supplied with a 0.9 mm tube
- Factory polished connectors
- Tested in according to i.hht current standards
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors geometry, Radius, fibre height, Apex Offset, Ferrule and fibre end faces
- Production according to i.hht certified ISO9001: 2002 and ISO14001: 2004
- RoHS according to i.hht 2002/95/ES



Pulling tube

Supplied without a drum at the lengths over 20m.



a: 275mm, b: 230mm, c: break-out length, could be specified, c: cable length, customer



Pulling tube with haul loop

IL = Insertion loss RL = Reflection loss		Standard Connectors				MTRJ Connectors	
		SM			MM	SM	MM
		SPC	UPC	APC	-	SPC	-
Threshold	IL (dB)	<0,35	<0,35	<0,35	<0,35	<0,5	<0,75
Typical value	IL (dB)	0,15	0,12	0,15	0,14	0,22	0,20
Threshold	RL (dB)	>45	>50	>60	-	>45	-
Typical value	RL (dB)	49	53	62	-	48	-

Gigacom Türkiye

Sales Office

:Haluk Türksoy Arkası Sok. No:2 K:1 D:3 Altunizade Üsküdar / İstanbul TR-34662 Tel : +90(216) 474 13 14 Fax : +90(216) 474 76 77 E-mail : info@gigacom-tr.com Web : www.gigacom-tr.com



## Ordering information

GKSUSU**0QBTxxxYE	Cable *F SM SC/UPC-SC/UPC xM QXAI Yellow LS0H
GKSASA**0QBTxxxYE	Cable *F SM SC/APC-SC/APCxM QXAI Yellow LS0H
GKFUFU**0QBTxxxYE	Cable *F SM FC/UPC-FC/UPC xM QXAI Yellow LSOH
GKFRFR**0QBTxxxYE	Cable *F SM FC/APCR-FC/UPCR xM QXAI Yellow LS0H
GKFNFN**0QBTxxxYE	Cable *F SM FC/APCN-FC/APCN xM QXAI Yellow LS0H
GKLULU**0QBTxxxYE	Cable *F SM LC/UPC/LC/UPC xM QXAI Yellow LSOH
GKLALA**0QBTxxxYE	Cable *F SM LC/APC-LC/APC xM QXAI Yellow LS0H
GKDUDU**0QBTxxxYE	Cable *F SM DIN/UPC-DIN/UPC xM QXAI Yellow LS0H
GKDADA**0QBTxxxYE	Cable *F SM DIN/APC-DIN/UPC xM QXAI Yellow LS0H
GKEUEU**0QBTxxxYE	Cable *F SM E2000/UPC-E2000/UPC xM QXAI Yellow LS0H
GKEAEA**0QBTxxxYE	Cable *F SM E2000/APC-E2000/UPC xM QXAI Yellow LS0H

<sup>\*:</sup> Number of connectors (24, 48)

Other variations/combinations after the agreement. See own data sheet for ordering information.

Gigacom Türkiye

Sales Office :Haluk Türksoy Arkası Sok. No:2 K:1 D:3 Altunizade Üsküdar / İstanbul TR-34662 Tel : +90(216) 474 13 14
Fax : +90(216) 474 76 77
E-mail : info@gigacom-tr.com
Web : www.gigacom-tr.com

x: Cable length (025=25m, 050=50m, 100=100m etc.)