

Patch cable ESCON (RSD) - GigaPATCH™

GigaPATCH™ ESCON patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- Meet IBM standards
- Production certified in i.hht. ISO9001:2002 and ISO14001:2004
- RoHS i.hht 2002/95/ES



Dimensions and characteristics

Standards		Telcordia GR-1435	
		SM	MM
IL = Insertion loss		SPC	-
RL = Reflection loss			
Threshold	IL (dB)	<0,5	<0,50
Typical value	IL (dB)	0,30	0,30
Threshold	RL (dB)	>45	-
Typical value	RL (dB)	48	-

Ordering Information

GCC6C60215xxxGY	Patch ESCON-ESCON MM 62,5/125/2000 (OM1) xM Gray LSOH
GCC5C50215xxxOR	Patch ESCON-ESCON MM 50/125/2000 (OM2) xM Orange LSOH
GCC3C30215xxxAQ	Patch ESCON-ESCON MM 50/125/2000 (OM3) xM Light blue LSOH
GCCSCS0215xxxYE	Patch ESCON/SPC-ESCON/SPC SM 9/125/2000 (OS1) xM Yellow LSOH

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

GigaCom reserves the right to make changes in this specification without prior notice.