

Patch cable LC - GigaPATCH™

GigaPATCH™ LC patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- The contacts are color coded i.hht IEC 60874-19 Beige for MM, Blue for SM and Green for APC
- Produktion certifierad i.hht ISO9001:2002 och ISO14001:2004
- RoHS i.hht 2002/95/ES



Dimensions and characteristics

Standards		IEC 61754-20, Telcordia GR-326, EN 50173-1:2002			
IL = Insertion loss		SM			MM
RL = Reflection loss		SPC	UPC	APC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,15	0,14
Threshold	RL (dB)	>45	>50	>60	-
Typical value	RL (dB)	49	53	62	-

Ordering Information

GCL6L60115xxxGY	Patch SPX LC-LC MM 62,5/125/2000 (OM1) xM Gray LSOH
GCL5L50115xxxOR	Patch SPX LC-LC MM 50/125/2000 (OM2) xM Orange LSOH
GCL3L30115xxxAQ	Patch SPX LC-LC MM 50/125/2000 (OM3) xM Light blue LSOH
GCLULU0115xxxYE	Patch SPX LC/UPC-LC/UPC SM 9/125/2000 (OS1) xM Yellow LSOH
GCLALA0115xxxYE	Patch SPX LC/APC-LC/APC SM 9/125/2000 (OS1) xM Yellow LSOH
GCA6A60215xxxGY	Patch DPX LCD-LCD MM 62,5/125/2000 (OM1) xM Gray LSOH
GCA5A50215xxxOR	Patch DPX LCD-LCD MM 50/125/2000 (OM2) xM Orange LSOH
GCA3A30215xxxAQ	Patch DPX LCD-LCD MM 50/125/2000 (OM3) xM Light blue LSOH
GCAUUA0215xxxYE	Patch DPX LCD/UPC-LCD/UPC SM 9/125/2000 (OS1) xM Yellow LSOH
GCAAAA0215xxxYE	Patch DPX LCD/APC-LCD/APC SM 9/125/2000 (OS1) xM Yellow LSOH

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

DPX: Clipped together

GigaCom reserves the right to make changes in this specification without prior notice