

Pigtail MU - GigaPATCH™

GigaPATCH™ MU Pigtail is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connector Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre end
- Produktion certifierad i.hht ISO9001:2002 och ISO14001:2004
- RoHS i.hht 2002/95/ES



Dimensions and characteristics

Standards		IEC 61754-6, Telcordia GR-326			
IL = Insertion loss RL = Reflection loss		SM			MM
		SPC	UPC	APC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,15	0,14
Threshold	RL (dB)	>45	>50	>60	-
Typical value	RL (dB)	49	53	62	-

Ordering Information

GCU6XX01111M5GY	Pigtail MU MM 62,5/125/900 (OM1) Tight buffer 1,5M Gray LSOH
GCU5XX01111M5OR	Pigtail MU MM 50/125/900 (OM2) Tight buffer 1,5M Orange LSOH
GCU3XX01111M5AQ	Pigtail MU MM 50/125/900 (OM3) Tight buffer 1,5M Light blue LSOH
GCUUXX01111M5BU	Pigtail MU/UPC SM 9/125/900 (OS1) Tight buffer 1,5M Blue LSOH
GCUAXX01111M5BU	Pigtail MU/APC SM 9/125/900 (OS1) Tight buffer 1,5M Blue LSOH

Other lengths / variations can be supplied on request.

GigaCom reserves the right to make changes in this specification without prior notice.