

Attenuator, Variabelt In-line patch

- Collimator using technology that provides better performance in comparison with conventional fibre technology
- Stable and high quality
- Attenuation range SM: 0dB~60dB
- Attenuation range MM: 0dB~40dB
- Very high resolution
- Very good reflection value
- PC and APC polishing
- Can be supplied with the most connector types 3
- Meet Telcordia GR-1221-CORE
- Minimum 500 connect/disconnecting



Dimensions and characteristics

Standards	Telcordia GR-910/GR-1221				
	SMF-28			MM 50/125, 62,5/125	
Fibre type					
Wavelength (nm)	1310 ±40	1550 ±40	1310/1550 ±40	850 ±40	1310 ±40
Attenuator range (dB)	0.6~60	0.6~60	0.8~60	0.8~40	0.8~40
Original loss(dB)	≤0.6	≤0.6	≤0.8	≤0.8	≤0.8
Return loss(dB)	≤50			≤30	
Adjusting precision (dB)	0.02				
Polarization Dependent Loss (dB)	≤0.15				
Ferrule material (contact)	Zirconia (ceramic)				
Number of connect/disconnecting	Min. 500				
Temperature range operating (°C)	0 ~+70				
Temperature range storage (°C)	-45 ~+85				
Humidity(%RH)	95				
Dimension (mm)	26 x 18 x 8				

Gigacom Türkiye

Sales Office :Haluk Türksoy Arkası Sok.
No:2 K:1 D:3 Altunizade
Üsküdar / İstanbul TR-34662

Tel : +90(216) 474 13 14
Fax : +90(216) 474 76 77
E-mail : info@gigacom-tr.com
Web : www.gigacom-tr.com