

Attenuator, LC fast plug-in

- Stable and high quality
- SM and MM
- Metal-ion doped fibre
- Low PDL
- Regardless of wavelength (xWDM compatible)
- Tolerate high power
- UPC and APC polishing
- Attenuation range from 1dB to 25dB
- 100% Control of the ferrule geometry, radius, fibre height, Apex offset, Ferrule and Fibre end.
- 100% visual inspection med 800x enlarge after polishing, before mounting and before delivery.
- Minimum 500 connect/disconnecting



Dimensions and characteristics

Standards		Telcordia GR-910/GR-1221	
Attenuation range (dB)	SM	1 ~25	
	MM	2 ~15	
Wavelength range (nm)	SM	1240 ~1625	
	MM	850	
Centre wavelength (nm)	SM	1310/1550	
	MM	850	
Ferrule material		Zirconia (Keramisk)	
Number of connect/disconnecting		Min. 500	
Reflection loss (dB)	UPC	≤-50	
	APC	≤-60	
	MM	N/A	
Attenuation tolerance (dB)	SM	1~10	±0,5
		11~25	±5%
	MM	2~10	±1,0
		15	±10%
Maximum Optic power (mW)		1000	
PDL (dB)		≤0,1	
Temperature (°C)	Storage	-40 ~+75	
	Operating	-40 ~+75	

Gigacom Türkiye

Sales Office :Haluk Türksoy Arkası Sok.
No:2 K:1 D:3 Altunizade
Üsküdar / İstanbul TR-34662

Tel : +90(216) 474 13 14
Fax : +90(216) 474 76 77
E-mail : info@gigacom-tr.com
Web : www.gigacom-tr.com

Ordering Information

2314210501	Attenuator SM LC/UPC 5dB
2314211001	Attenuator SM LC/UPC 10dB
2314211501	Attenuator SM LC/UPC 15dB
2314212001	Attenuator SM LC/UPC 20dB
2314310501	Attenuator SM LC/APC 5dB
2314311001	Attenuator SM LC/APC 10dB
2314311501	Attenuator SM LC/APC 15dB
2314312001	Attenuator SM LC/APC 20dB
2314140501	Attenuator MM 50/125 LC 5dB
2314141001	Attenuator MM 50/125 LC 10dB
2314141501	Attenuator MM 50/125 LC 15dB
2314142001	Attenuator MM 50/125 LC 20dB

Other variations are available upon request.

Gigacom Türkiye

Sales Office :Haluk Türksoy Arkası Sok.
No:2 K:1 D:3 Altunizade
Üsküdar / İstanbul TR-34662

Tel : +90(216) 474 13 14
Fax : +90(216) 474 76 77
E-mail : info@gigacom-tr.com
Web : www.gigacom-tr.com